



Industrial Monitor

17" Open Frame Monitor

17"

16M

260 cd/m²



Display	
Display Type	17" SXGA TFT LCD
Resolution	1280 (H) x 1024 (V)
Pixel Pitch	0.264 (H) x 0.264 (V) (mm)
Display Color	16M
Brightness	260 cd/m ²
Contrast Ratio	450:1
Viewing Angle	L/R:-70° ~ +70°, U/D:-70° ~+70°
Response Time	8 (Tr+Tf) (ms)
Back Light MTBF	50,000 (hour)
Construction	Heavy duty steel chassis with VESA 75/100mm standard screw holes
OS Support	MS DOS, Windows 98/SE, Windows NT4.0, Windows 2000, Windows XP
Menu OSD	Yes

Order Information	
AT-OP17	17" Open Frame
AT-OP17TS	17" Open Frame with Touchscreen, RS232
AT-OP17TU	17" Open Frame with Touchscreen, USB
Option	
AT-OP-EXAV	AV Connector instead serie
AT-OP-EXDVI	DVI instead serie

I/O	
Power Input	External 48WDC 12V power adapter
Audio input	Line-in
Video input	15 pin D-SUB, AV input (Optional)

Touch Screen	
Type	Five-wire Analog resistive
Controller	RS-232 (AT-OP17TS) USB (AT-OP17TU)
Resolution	continuous
Light transmission	79%or more
Power consumption	<5V @100Ma

Mechanical and Environmental	
Operating temperature	0 °C~ 45°C
Storage temperature	-20°C~60°C
Storage humidity	10% ~ 95%@40°C,Non-condensing
Dimensions	428.6 x 342.6 x 50 mm
Gross Weight	8.4 (kg)

DRAWING

