



### Features

- Intel Atom Processor D2550 1.86GHz , L2 Cache 1MB
- Support 2 x SO-DIMM 204pin, up to 4GB DDRIII 800/1066MHz FSB
- Fanless Solution
- 2 x 2.5" SATA HDD space
- 1 x External CF slot
- Support 9~32V DC power input and AC power input

### Specifications

#### System

Processor	Intel Atom Processor D2550 1.86GHz , L2 Cache 1MB
System Chipset	Intel NM10 Express
External I/O Port	Rear I/O Side 1 x RS-232 (COM1) 1 x RS-232 (COM2) 1 x DB15 VGA 4 x USB 2.0 Ports 2 x Ethernet RJ45 LAN Port 1 x 9~32V DC Power input 1 x Audio Ports (MIC-in, Line out) 1 x 2 Pin Power Switch (terminal block) 2 x LED Indication (Power/HDD) 1 x Power button switch 1 x CF Slot by USB 1 x COM RS-422/485 (COM3, default:RS-485) 1 x COM RS-232 (COM4) 1 x 10 pins terminal block for 1 Ground/VCC/ 4 in & out DIDO

System Memory	Support 2 x SO-DIMM 204pin, up to 4GB DDRIII 800/1066MHz FSB
Storage	Default 2 x 2.5" SATA HDD space 1 x External CF slot 2 x 2.5" SATA HDD Space
DVD Driver	Optional function (Not available if 2 HDD has been used)
Power Input	On board DC 9~32V/AC power input
Expansion Slots	1 x PCI and PCIe x1 slots or 2 x PCI slots
OS Support	Win 7 Pro, WIN CE 6.0, Windows embedded standard 7

#### Mechanical







Construction	Black Steel and Aluminum Heatsink
Color	Black
IP Rating	Wall mount
Mounting	Option: Din Rail mount (single or dual)
Dimension	203.5 (W)x 211.2 (H)x 153.2 (D) mm 211.2 (W)x 203.5 (H)x 157.3 (D) mm (w DVD Device)

#### Environmental

Operating Temperature	0°C to 50°C
Storage Temperature	-20~60 °C
Storage Humidity	10~90% @40 °C non-condensing
Certificate	CE/FCC Class A

### Dimensions

ACS-2645  
DC IN  
DVD



ACS-2645  
AC IN  
DVD

