

# MONITOR

## AT-IP17



**Industrial LCD monitor**  
**Aluminium bezel front**  
**IP65 front**  
**resistive touch screen optional**  
**VGA and DVI**

### Specification

#### System Specifications


Viewable Size Image	17"
Active Display Area (mm)	337.9(H)x270.3(V)
Pixel Pitch (mm)	0.263(H)x0.263(V)
Number of Pixels	1280 x 1024
Contrast Ratio	800:1
Display Color	16,7M
Brightness (CD/m <sup>2</sup> )	300CD/m <sup>2</sup>
Viewing Angle (CR >=10)	160/160
Synchronization Range Horizontal / Vertical	31.5~48.1KHz/56~75Hz
Recommended Resolution	1280x1024@60Hz, 75Hz
Signal Connector	15 pin D-sub / DVI-D
Power Source	12V - 4A
Power Consumption	13.3W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	No
Optional DVI Input	Yes
Optional Touch Screen	optional , SAW,Resistance

### Order Information

AT-IP17	17" Industrial Monitor
AT-IP17TU	17" Industrial Monitor, with res.touch USB

### Accessories

inclusiv: DC 12V - AC 220V/110V Power Adapter, 220V europe power cord, Nuts for wallmounting,





Monitor

**AT-TI17**

Drawing

