

Selection Guide

CE Series



	AT-CECM16	AT-CEPM18
Specification		
System		
CPU	Intel Celeron M 1.6 GHZ CPU	Intel Pentium M 1.8 GHZ CPU
Chipset	Intel 82852GM + ICH4	
Memory	1 x 184-pins DDR DIMM up to 1GB	
Fanless/Fan	Fanless cooling system	
Watchdog Timer	Generates system reset; 256 levels	
Power Supply	DC 11~28V wide-range power input	
Operation System	Windows XP, XP Embedded, Windows CE and Linux	
HDD	Space for 1 x 2.5" HDD, 1 x CF socket (optional)	
I/O Ports		
USB	4 x USB 2.0	
Keyboard/Mouse	1 x PS/2 ports for keyboard and mouse	
LAN	2 x 10/100 Mbps LAN (RJ45)	
Audio	Line-out, Mic	
Serial Ports	3 x RS-232 (COM1~2)	
Parallel Port	1 x LPT(SPP/EPP/ECP mode), optional	
Graphic Ports	1 x VGA Intel 852GM + ICH4	
Expansion	1 x PCI slot	



Embedded System

CE Series

Pentium M Celeron M Fanless

4 USB 3 COM 2 LAN PCI Audio VGA



- ✓ Fanless design
- ✓ Intel Pentium M & Celeron M processors
- ✓ Dual LAN, 3 x COM ports, 4 x USB ports
- ✓ Space for 2.5" slim type HDD and 1 CF card slot
- ✓ One PCI expansion slot
- ✓ DC 11~28V wide-range power input

System	
CPU	Intel Pentium M & Celeron M processors
Chipset	Intel 82852GM + ICH4
Memory	1 x 184-pins DDR DIMM up to 1GB
Fanless/Fan	Fanless cooling system
Watchdog Timer	Generates system reset; 256 levels
Power Supply	DC 11~28V wide-range power input
Operation System	Windows XP, XP Embedded, Windows CE and Linux
Dimension (WxHxD)	240 x 104 x 230mm
Certificate	FCC / CE
HDD	Space for 1 x 2.5" HDD, 1 x CF socket (optional)

I/O Ports	
USB	4 x USB 2.0
Keyboard/Mouse	1 x PS/2 ports for keyboard and mouse
LAN	2 x 10/100 Mbps LAN (RJ45)
Audio	Line-out, Mic
Serial Ports	3 x RS-232 (COM1~2)
Parallel Port	1 x LPT (SPP/EPP/ECP mode), optional
Graphic Port	1 x VGA Intel 852GM + ICH4
ExpAnsiion	1 x PCI slot

Mechanical Specifications	
Construction	Aluminum + Heavy-duty steel chassis
Mounting	Wall mount

Environment	
Operating Temp.	0°~60°C
Storage Tmp.	0°~ 80°C
Humidity	20% ~ 90%

Ordering Information	
AT-CECM16	Embedded PC, Intel Celeron M 1.6 GHZ, 256MB, 40GB
AT-CEPM18	Embedded PC, Intel Pentium M 1.8 GHZ, 256MB, 40GB
Option	
AT-CE-EX512	512MB RAM instead serial
AT-CE-EXLPT	LPT Port
AT-CE-CF4	CompactFlash 4GB instead serial
AT-CE-CF8	CompactFlash 8GB instead serial

1 Industrial Panel PC

2 Embedded System

3 Industrial Monitor

4 LCD Monitor Console

5 Rackmount Panel